

J-208

- Pocketsized, full function large display.
- Wide range, high performance, low price.
- Both contact & non-contact.
- High accuracy, fast response.

Measuring range	-30~500°C
Display range	-64~1400°C
Field of view	Φ 50/400mm(D:S=8:1)
Spectral response	8~14μm
Resolution	0.1°C/°F
Emissive	ε0.10~1.0(Adjustable)
Auto OFF	60sec
Response time	T90=0.5sec
Measuring accuracy	0.2% of reading±1°C
Sighting method	Non-coaxial laser spot
Main functions	MAX,MIN,AVG,DIF mode, SCAN,HI/LOW alarm, Backlight,Probe input
Power	2AA1.5V Alkaline
Battery life	>300hrs



Operating Temp	-10~50°C
Operating Humidity	
Storage Temp	-27~70°C
Dimensions	138x39x28mm
Weight	130g



TM-8811 with wall sound speed feature

Measurement Range	1.5~200mm 0.06~8inch
Sensor Type	Ultrasonic
Materials	11 Types
Velocity Range	500~9000 m/s
Calibration Block	Included
Accuracy	±(0.5%n+0.2)
Power Supply	4x1.5v AA(UM-3)BATTERY
Dimensions	161x69x32mm

Authorised Channel Partner in India

Universal engineers

BE-200, Lane No. 6,
Hari Nagar, New Delhi -110064
Tel./Fax : 91-11-25127461, 25496072, 9958004710
GSM: 9810269366, 9810589043
E-mail: dynamic6@vsnl.com, contact@ues.net.in
www.ues.net.in